



M100 ORD LOC

Depureco Industrial Vacuums USA

19121 Marketplace Avenue, Building 1, Suite 165
Plum Creek Business Park • Kyle • TX 78640

www.depurecousa.com
info@depurecousa.com



3.3 HP
POWER


3800 in²
FILTER

26 gal Bin
CAPACITY

Dirty side volume of less than 0.2 m3 (8 ft3)



3 POWERFUL BY-PASS MOTORS
120V
Max Airflow= 336 CFM
Max Depression= 98 inH2O



Head with double stage filtration system.



M CLASS
Antistatic star filter



MTF OPTIONAL
For difficult and sticky dust.



3720.01 in²



COMPLETELY GROUNDED COMPONENTS



MANUAL SHAKER CLEANING SYSTEM

Smart handle for shaking the filter aggressively to release dust.



26 gal

DETACHABLE BIN ON WHEELS



DIRTY SIDE VOLUME BELOW 8 FT³




OPTIONAL H 14 HEPA FILTER




4400 in²

OPTIONAL TANGENTIAL INLET




INLET WITH DEFLECTOR




HIGHLY TRANSPORTABLE

WET & DRY FIXED BRUSH FLOOR TOOL

TILTABLE KIT FOR DUST IN BIN



31 in



26 in

60 in

Weight: 176 lbs



SPEC SHEET

	Units	M 100 ORD LOC
Motors Type		3 - By-Pass
Power	HP	3.3
Voltage Frequency	V/Hz	120/60
Maximum vacuum	inH2O	98
Maximum air flow	CFM	336
Inlet	Ø in	2.75
Noise level - (EN ISO 3744)	dB(A)	72
Bin capacity	gal	26
Dimensions	in	26 X 31
Height	in	60
Weight	lb	176
Primary filter		
Type		Star filter
Surface area Diameter	in² in	3.800
(Class EN 60335-2-69)		M Class
Media		Antistatic Polyester
Filter cleaning		Manual Shaker
Absolute filter		
Surface area	in²	4.400
(Class - EN 1822)		H14
Media		Fiberglass

NORMATIVE REFERENCES

COMPLIANT TO

- UL1017
- CSA22.2#243

COMPLIANT TO




UL1017
The unit is suitable for collecting combustible dust in Unclassified (Ordinary) Locations, in accordance with US regulations.

CSA22.2#243
Compliance for handling combustible dust in unclassified areas for the Canadian market.

OPTIONAL FILTERS



BFL
M class filter



ANT M
Antistatic filter




MTF
Teflon filter



NOMEX
482° F Resistant filter



PTFE
PTFE filter



H 14
Absolute filter

OPTIONAL



AB
Accessory basket



TAN
Tangential inlet + cyclone



BX
AISI 304 stainless stell bin



GX
AISI 304 BIN AND CHAMBER



TX
AISI 304 STRUCTURE, BIN AND CHAMBER



FLT
Floating device for liquids


ACCESSORIES



Iron reducer
Ø 2.75 / 2 in



Wet & Dry Kit
Ø 2 in



Starter Kit
Ø 2 in